

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (currently amended): A method for manufacturing a distal protection device, comprising: braiding a plurality of filaments to form a distal protection element having a first end region having a first thickness and a second end region having a second thickness; and reducing at least one of the first and second thicknesses in at least a portion of the first and second end regions.

Claim 2 (Original): The method of claim 1, further comprising: heat treating the filaments of the braided distal protection element.

Claim 3 (Original): The method of claim 2, wherein the heat treating step is performed prior to the reducing step.

Claim 4 (Original): The method of claim 2, wherein the heat treating step is performed after the reducing step.

Claim 5 (Original): The method of claim 1, wherein the distal protection element is a capture element.

Claim 6 (Original): The method of claim 1, wherein the distal protection element is an occluder.

Claim 7 (canceled)

Claim 8 (Original): The method of claim 1, wherein the reducing step comprises electropolishing at least a portion of one of the filaments.

Claim 9 (Original): The method of claim 1, wherein the reducing step comprises etching at least a portion of one of the filaments.

Claim 10 (Original): The method of claim 7, wherein the etching step is selected from the group consisting of photo etching, chemical etching and laser etching.

Claim 11 (Original): The method of claim 1, wherein the reducing step comprises acid pickling at least a portion of one of the filaments.

Claim 12 (Original): The method of claim 1, wherein the reducing step comprises mechanically grinding at least a portion of one of the filaments.

Claim 13 (currently amended): The method of claim 1, wherein the reducing step comprises cutting and removing a portion of at least one of the filaments in at least one of the first or second end ~~region~~ regions.

Claim 14 (Original): The method of claim 1, wherein the filaments comprise nitinol wires.

Claim 15 (Original): The method of claim 1, wherein the filaments comprise drawn-filled tubing wires.

Claim 16 (currently amended): The method of claim ~~[[13]]~~ 15, wherein the reducing step comprises removing an outer casing of at least one of the drawn-filled tubing wires along at least a portion of the wire.

Claim 17 (currently amended): The method of claim ~~[[14]]~~ 15, wherein the reducing step further comprises etching a core of at least one of the drawn-filled tubing wires.

Claim 18 (Original): The method of claim 1, wherein the filaments comprise a combination of nitinol wires and drawn-filled tubing wires.

Claim 19 (Original): The method of claim 1, wherein the filaments are made of material selected from the group consisting of metal, thermoplastic polymer, thermoset polymer, ceramics and glass.

Claim 20 (Original): The method of claim 1, wherein the reducing step gradually reduces one of the first and second thicknesses in at least one of the first and second end regions.

Claim 21 (Original): The method of claim 18, wherein the reducing step creates a stepped profile in at least one of the first and second end regions.

Claim 22 (Original): The method of claim 1, wherein the reducing step involves removing material from at least one of the first and second end regions in a spiral pattern.

Claim 23 (Original): The method of claim 1, wherein the reducing step involves removing material from at least one of the first and second end regions in a longitudinally striped pattern.

Claim 24 (Original): A method for making a braided distal protection element of a distal protection device, comprising: braiding a plurality of heat set filaments to form a braided distal protection element having a first end region and a second end region; heat treating the filaments; dipping at least one of the first and second end regions into an acid pickling solution; and attaching a marker band around at least one of the first and second end regions.

Claim 25 (canceled)

Claim 26 (Original): A distal protection device comprising: a distal protection element having a first end region having a first wall thickness and a second end region having a second wall thickness, wherein at least a portion of at least one of the first and second end regions has been selectively removed.

Claim 27 (Original): The distal protection device of claim 26, wherein a marker band is disposed around at least one of the first and second end regions.